

PART NO. **19374720**

Dexron III

BENEFITS

- Good frictional characteristics and wear protection help provide maximum cold temperature performance, excellent friction retention, and smooth shifting
- High oxidation resistance helps with rust and corrosion as well as fluid change intervals
- Wide range of seal compatibility – can be used in an extensive variety of vehicles/transmission
- Meets requirements for foam protection and helps protect against metal-to-metal friction and wear within the transmission

PRODUCT FEATURES

ACDelco Automatic Transmission Fluid Type III (H) is designed to protect and extend the life of automatic transmissions. It provides smooth shift performance and excellent protection against corrosion and wear.

SDS

CLASSIFICATION: Acute aquatic toxicant: Category 2.
Chronic aquatic toxicant: Category 3.

Environmental Hazards: Toxic to aquatic life (H401).
Harmful to aquatic life with long lasting effects (H412).

PHYSICAL AND CHEMICAL PROPERTIES:

Color: Red

Physical State: Liquid

Odor: Petroleum odor

pH: Not Applicable

Vapor Pressure: <0.01 mmHg Maximum @ 37.8 °C (100 °F)

Vapor Density (Air = 1): >1 Minimum

Boiling Point: 315°C (599°F) Minimum

Solubility: Soluble in hydrocarbons; insoluble in water

Density: 0.855 kg/l @ 15°C (59°F) (Typical)

Viscosity: 7.3 mm²/s @ 100°C (212°F) (Typical)

FLAMMABLE PROPERTIES:

Flashpoint: (Cleveland Open Cup) 190 °C (374 °F) Minimum